This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Currently Amended) A tool ~~(1)~~ for connection and disconnection of a cargo item ~~(8)~~, in which the tool ~~(1)~~ comprises a suspension ~~(2)~~ and a lifting hook ~~(4)~~, and in which the lifting hook ~~(4)~~ is rotatably connected, about its suspension axis ~~(40)~~, to the suspension ~~(2)~~, ~~characterized in that~~wherein the lifting hook ~~(4)~~ is connected to an actuator ~~(22, 28, 32, 70)~~ via a transmission ~~(44, 46, 48, 50, 54, 60)~~, the actuator ~~(22, 28, 32, 70)~~ being arranged to allow it to rotate the lifting hook ~~(4)~~ about the suspension axis ~~(40)~~.

2. (Currently Amended) The tool ~~(1)~~ according to claim 1, ~~characterized in that~~wherein the lifting hook ~~(4)~~ is articulately connected to a middle centre-cross of a pair of double-scissors ~~(22)~~ by means of a middle bearing ~~(24)~~, a lower centre-cross of the pair of double-scissors ~~(22)~~ being articulately connected to the suspension ~~(2)~~ of the tool ~~(1)~~ by means of a lower bearing ~~(26)~~, and wherein a transmission ~~(44, 46, 48, 50, 54, 60)~~ provided for the rotating function of the hook ~~(1)~~ about its suspension axis ~~(40)~~ is releasably connectable to an upper centre-cross of the pair of scissors by means of an upper bearing ~~(30)~~.

3. (Currently Amended) The tool ~~(1)~~ according to claim 2, ~~characterized in that~~wherein the pair of double-scissors ~~(22)~~ is resiliently biased in the direction of its extended position by means of a spring ~~(32)~~.

4. (Currently Amended) The tool ~~(1)~~ according to claim 1, ~~characterized in that~~wherein a load-bearing guide rod ~~(20)~~ movable in the suspension ~~(2)~~ is lockable relative to the suspension ~~(2)~~.

5. (Currently Amended) The tool ~~(1)~~ according to claim 4, ~~characterized in that~~wherein the guide rod ~~(20)~~ is arranged to be locked in the suspension ~~(2)~~ by means of a first locking arm ~~(64)~~.

6. (Currently Amended) The tool ~~(1)~~ according to claim 5, ~~characterized in that~~wherein the first locking arm ~~(64)~~ is remotely releasable by means of a first trigger ~~(68)~~.

7. (Currently Amended) The tool ~~(1)~~ according to claim 6, ~~characterized in that~~wherein the first trigger ~~(68)~~ is activated by means of a radio transmitter ~~(78)~~, a receiver ~~(80)~~ and a control unit ~~(74)~~.

8. (Currently Amended) The tool ~~(1)~~ according to claim 1, ~~characterized in that~~wherein a second link arm ~~(46)~~, which is arranged to allow it to rotate the lifting hook ~~(4)~~ about the suspension axis ~~(40)~~ of the hook ~~(4)~~ by means of rotating a first link arm ~~(44)~~ about a connection point, is connected to a guide ~~(50)~~ by means of a locking joint ~~(48)~~.

9. (Currently Amended) The tool ~~(1)~~ according to claim 8, ~~characterized in that~~wherein the direction between the connection point of the locking joint ~~(48)~~ substantially is perpendicular relative to the longitudinal axis of the second link arm ~~(46)~~ and a guideway ~~(52)~~ for the guide ~~(50)~~ when the locking joint ~~(48)~~ is in its locking position.